


# PROKTES

## Plastic Frame Fine Dust V Compact Filter | EPA



Filter Media	Micro Glass Fibre Paper			
Frame Material	Plastic			
Average Gravimetric Efficiency	40-60 %	60-80 %	80-90 %	90-95 %
Classification (EN 779:2002)	F6	F7	F8	F9
Eurovent Class	EU6	EU7	EU8	EU9
Initial Pressure Drop	100	115	125	155
Final Pressure Drop	600 Pa			
Max. Temperature	100 °C			
Max. Moisture	100 %			

Product Code	Dimensions (WxHxD)	Media Area (m <sup>2</sup> )	Air Flow (m <sup>3</sup> /h)	Press. Drop (Pa)
<b>292-F6</b>				
KMF-PWS-287/592/292-F6	287x592x292	9	2125	100
KMF-PWS-490/592/292-F6	490x592x292	15	3400	100
KMF-PWS-592/592/292-F6	592x592x292	18	4250	100
<b>292-F7</b>				
KMF-PWS-287/592/292-F7	287x592x292	9	2125	115
KMF-PWS-490/592/292-F7	490x592x292	15	3400	115
KMF-PWS-592/592/292-F7	592x592x292	18	4250	115
<b>292-F8</b>				
KMF-PWS-287/592/292-F8	287x592x292	9	2125	125
KMF-PWS-490/592/292-F8	490x592x292	15	3400	125
KMF-PWS-592/592/292-F8	592x592x292	18	4250	125
<b>292-F9</b>				
KMF-PWS-287/592/292-F9	287x592x292	9	2125	155
KMF-PWS-490/592/292-F9	490x592x292	15	3400	155
KMF-PWS-592/592/292-F9	592x592x292	18	4250	155
<b>292-H10</b>				
KMF-PWS-287/592/292-H10	287x592x292	9	2125	200
KMF-PWS-490/592/292-H10	490x592x292	15	3400	200
KMF-PWS-592/592/292-H10	592x592x292	18	4250	200
<b>292-H13</b>				
KMF-PWS-287/592/292-H13	287x592x292	9	2125	220
KMF-PWS-490/592/292-H13	490x592x292	15	3400	220
KMF-PWS-592/592/292-H13	592x592x292	18	4250	220

### Advantages

- Economic operation and high filtration surface
- Long operation life
- High dust holding capacity
- Low pressure drop
- Compact, incinerable
- Rapid installation

